

## "MKSII" Series



- Pure sine wave inverter
- Built-in MPPT solar charge controller
- Selectable input voltage range for home appliances and personal computers
- Selectable charging current based on applications
- Configurable AC/Solar input priority via LCD setting
- Compatible to mains voltage or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Battery equalization for optimized battery performance and lifecycle
- Cold start function
- Parallel operation with up to 9 units only available for 5KVA

MODEL	SI1000MKS
Rated Power	5000VA / 5000W
Parallel Capability	Yes, 9 unit
<b>INPUT</b>	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt. mode)	230VAC $\pm$ 5%
Surge Power	2000VA
Efficiency (Peak)	90%
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)
Waveform	Pure sine wave
<b>BATTERY</b>	
Battery voltage	48 VDC
Floating Charge Voltage	54 VDC
Overcharge Protection	63 VDC
<b>SOLAR CHARGE &amp; AC CHARGER</b>	
Maximum PV Array Power	4500W
MPP Range @ Operating Voltage	120 VDC ~ 430 VDC
Maximum PV Array Open Circuit Voltage	450 VDC
Maximum Solar Charge Current	80A
Maximum AC Charge Current	80A
Maximum Charge Current	80A
<b>PHYSICAL</b>	
Dimension D x W x H (mm)	120 x 295 x 468
Net Weight (kgs)	11
<b>ENVIRONMENT</b>	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	0°C - 55°C
Storage Temperature	-15°C - 60°C